



410-539-8000

Serving MD • VA • DE • PA • DC

PIPE & STEEL SUPPLY, LLC

Dimensions & Weights for Plain End Pipe

1301 Wicomico Street • P.O. Box 6367  
Baltimore, MD 21230

www.dspipeandsteel.com

Fax: 410-539-4819  
Toll Free: 800-368-8880

NORMAL PIPE SIZE INCHES	OUTSIDE DIAMETER INCHES	I.P.S.	SCHEDULE	WALL INCHES	INSIDE DIAMETER INCHES	WT/FT-POUNDS
1/8	.405	40	10S	.049	.307	.1863
			40S Std.	.068	.269	.2447
			80S X-Hvy.	.095	.215	.3145
1/4	.540	40	10S	.065	.410	.3297
			40S Std.	.088	.364	.4248
			80S X-Hvy.	.119	.302	.5351
3/8	.675	40	10S	.065	.545	.4235
			40S Std.	.091	.493	.5676
			80 X-Hvy.	.126	.423	.7388
1/2	.840	40	5S	.065	.710	.5383
			10S	.083	.674	.6710
			40S Std.	.109	.622	.8510
			80S X-Hvy.	.147	.546	1.088
			XX-Hvy.	.294	.252	1.714
3/4	1.050	40	5S	.065	.920	.6838
			10S	.083	.884	.8572
			40S Std.	.113	.824	1.131
			80S X-Hvy.	.154	.742	1.474
			XX-Hvy.	.308	.434	2.441
1	1.315	40	5S	.065	1.185	.8678
			10S	.109	1.097	1.404
			40S Std.	.133	1.049	1.679
			80S X-Hvy.	.179	.957	2.172
			XX-Hvy.	.358	.815	2.844
1 1/4	1.660	40	5S	.065	1.530	1.107
			10S	.109	1.442	1.806
			40S Std.	.140	1.380	2.273
			80S X-Hvy.	.191	1.278	2.997
			XX-Hvy.	.382	1.160	3.765
1 1/2	1.990	40	5S	.065	1.770	1.274
			10S	.109	1.682	2.085
			40S Std.	.145	1.610	2.718
			80S X-Hvy.	.200	1.500	3.631
			XX-Hvy.	.400	1.338	4.859
2	2.375	40	5S	.065	2.245	1.604
			10S	.109	2.157	2.638
			40S Std.	.154	2.067	3.653
			80S X-Hvy.	.218	1.939	5.022
			XX-Hvy.	.436	1.689	7.462
2 1/2	2.875	40	5S	.083	2.709	2.475
			10S	.120	2.635	3.531
			40S Std.	.203	2.469	5.793
			80S X-Hvy.	.276	2.323	7.661
			XX-Hvy.	.552	2.125	10.01
3	3.500	40	5S	.083	3.334	3.029
			10S	.120	3.260	4.332
			40S Std.	.216	3.068	7.576
			80S X-Hvy.	.300	2.900	10.25
			XX-Hvy.	.600	2.624	14.32

NORMAL PIPE SIZE INCHES	OUTSIDE DIAMETER INCHES	I.P.S.	SCHEDULE	WALL INCHES	INSIDE DIAMETER INCHES	WT/FT-POUNDS	
3 1/2	4.000	5	5S	.083	3.834	3.472	
			10S	.120	3.760	4.973	
			40S Std.	.226	3.548	9.109	
			80 X-Hvy.	.318	3.364	12.50	
4	4.500	40	XX-Hvy.	.636	2.728	22.85	
			80S	5S	.083	4.334	3.915
				10S	.120	4.260	5.613
				40S Std.	.237	4.026	10.79
80S X-Hvy.	.337	3.826		14.98			
4 1/2	5.000	80	XX-Hvy.	.674	3.624	19.00	
			5S	.531	3.438	22.51	
			10S	.710	3.152	27.54	
			40S Std.	.247	4.506	12.53	
5	5.563	40	80S X-Hvy.	.355	4.290	17.61	
			XX-Hvy.	.710	3.580	32.43	
			80	5S	.109	5.345	6.349
				10S	.134	5.295	7.770
40S Std.	.258	5.047		14.62			
80 X-Hvy.	.375	4.813		20.78			
6	6.625	120	XX-Hvy.	.750	4.563	27.04	
			5S	.625	4.313	32.96	
			10S	.864	4.063	38.55	
			40S Std.	.280	6.407	7.585	
7	7.625	80	10S	.134	6.357	9.289	
			40S Std.	.280	6.065	18.97	
			80S X-Hvy.	.432	5.761	28.57	
			XX-Hvy.	.875	5.491	36.39	
8	8.625	160	XX-Hvy.	.864	5.189	45.35	
			5S	.719	4.897	53.16	
			10S	.109	7.023	23.57	
			40S Std.	.301	6.625	38.05	
9	9.625	40	80S X-Hvy.	.500	5.875	63.08	
			5S	.109	8.407	9.914	
			10S	.148	8.329	13.40	
			20	.250	8.125	22.36	
10	10.750	60	30	.277	8.071	24.70	
			40S Std.	.322	7.981	28.55	
			40	.406	7.813	35.64	
			80S X-Hvy.	.500	7.625	43.39	
11	11.750	80	100	.594	7.439	50.95	
			120	.719	7.189	60.71	
			140	.812	7.001	67.76	
			XX-Hvy.	.875	6.875	72.42	
12	12.750	100	XX-Hvy.	.906	6.813	74.69	
			40S Std.	.342	8.941	33.90	
			80S X-Hvy.	.500	8.625	48.72	
			XX-Hvy.	.875	7.875	81.77	
13	13.750	120	5S	.134	10.482	15.19	
			10S	.165	10.420	18.70	
			20	.250	10.250	28.04	
			30	.307	10.136	34.24	
14	14.750	140	40S Std.	.365	10.020	40.48	
			80S X-Hvy.	.500	9.750	54.74	
			80	.594	9.564	64.43	
			100	.719	9.314	77.03	
15	15.750	160	120	.844	9.064	89.29	
			140	1.000	8.750	104.13	
			160	1.125	8.500	115.64	



**410-539-8000**  
 Serving MD • VA • DE • PA • DC

**PIPE & STEEL SUPPLY, LLC**

**Dimensions & Weights for Plain End Pipe**

1301 Wicomico Street • P.O. Box 6367  
 Baltimore, MD 21230

[www.dspipeandsteel.com](http://www.dspipeandsteel.com)

Fax: 410-539-4819  
 Toll Free: 800-368-8880

NORMAL PIPE SIZE INCHES	OUTSIDE DIAMETER INCHES	I.P.S.	SCHEDULE	WALL INCHES	INSIDE DIAMETER INCHES	WT./FT. POUNDS
11	11.750	40	40S Std.	.375	11.000	45.55
		80	X-Hvy.	.500	10.750	60.07
			XX-Hvy.	.875	10.000	101.63
12	12.750		5S	.165	12.420	22.18
			10S	.180	12.390	24.20
		20		.250	12.250	33.38
		30		.330	12.090	43.77
			40S Std.	.375	12.000	49.56
		40		.406	11.938	53.52
			80S X-Hvy.	.500	11.750	65.42
		60		.562	11.626	73.15
		80		.688	11.376	88.63
		100		.844	11.064	107.32
		120		1.000	10.750	125.49
140		1.125	10.500	139.67		
		1.312	10.126	160.27		
14	14.000	10		.250	13.500	36.71
		20		.312	13.376	45.61
		30	Std.	.375	13.250	54.57
		40		.438	13.124	63.44
			X-Hvy.	.500	13.000	72.09
		60		.594	12.814	85.05
		80		.750	12.500	106.13
		100		.938	12.126	130.85
		120		1.094	11.814	150.90
		140		1.250	11.500	170.21
		160		1.406	11.188	189.10
16	16.000	10		.250	15.500	42.05
		20		.312	15.376	52.27
		30	Std.	.375	15.250	62.58
		40		.500	15.000	82.77
			X-Hvy.	.656	14.688	107.50
		60		.844	14.314	136.61
		80		1.031	13.938	164.82
		100		1.219	13.564	192.43
		120		1.438	13.124	223.64
		140		1.594	12.814	245.25
		160				

NORMAL PIPE SIZE INCHES	OUTSIDE DIAMETER INCHES	I.P.S.	SCHEDULE	WALL INCHES	INSIDE DIAMETER INCHES	WT./FT. POUNDS
18	18.000	10		.250	17.500	47.39
		20		.312	17.376	58.94
			Std.	.375	17.250	70.59
		30		.438	17.124	82.15
			X-Hvy.	.500	17.000	93.45
		40		.562	16.876	104.67
		60		.750	16.500	138.17
		80		.938	16.126	170.92
		100		1.156	15.688	207.96
		120		1.375	15.250	244.14
		140		1.562	14.876	272.22
160		1.781	14.438	308.50		
20	20.000	10		.250	19.500	52.73
		20	Std.	.375	19.250	78.60
		30		.500	19.000	104.13
		40	X-Hvy.	.594	18.814	123.11
		60		.812	18.376	166.40
		80		1.031	17.938	208.87
		100		1.281	17.438	256.10
		120		1.500	17.000	296.37
140		1.750	16.500	341.09		
160		1.969	16.064	379.17		
22	22.000	10		.250	21.500	58.07
		20	Std.	.375	21.250	86.61
		30		.500	21.000	114.81
		60	X-Hvy.	.875	20.250	197.41
		80		1.125	19.750	250.81
		100		1.375	19.250	302.88
		120		1.625	18.750	353.61
		140		1.875	18.250	403.00
160		2.125	17.750	451.06		
24	24.000	10		.250	23.500	63.41
		20	Std.	.375	23.250	94.62
			X-Hvy.	.500	23.000	125.49
		30		.562	22.876	140.68
		40		.688	22.626	171.29
		60		.969	22.064	238.35
		80		1.219	21.564	296.58
		100		1.531	20.938	367.39
		120		1.812	20.376	429.39
		140		2.062	19.876	483.10
		160		2.344	19.314	542.13